

Page 1 of 8

FOSTER 30-35 802256PM

SAFETY DATA SHEET

REVISION DATE: 09-26-2016

SUPERSEDES: 12-19-2014

SECTION 1: IDENTIFICATION OF THE PRODUCT AND SUPPLIER

PRODUCT INFORMATION

PRODUCT: PRODUCT DESCRIPTION: INTENDED USE: PRODUCT IDENTIFIER: FOSTER 30-35 Coating 802256PM

COMPANY INFORMATION

H.B. Fuller Construction Products Inc. 1105 S. Frontenac Street Aurora, IL 60504 Phone: 1-800-552-6225

> Medical Emergency Phone Number (24 Hours): 1-888-853-1758 Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

SECTION 2: HAZARDS IDENTIFICATION

GHS Hazard Symbols:



GHS Signal Word:	Warning		
GHS	Skin Sensitisation Category 1; Hazardous to the aquatic environment - Acute Category 1;		
Classification:	Carcinogenicity Category 2; Hazardous to the aquatic environment - Chronic Category 2;		
	Flammable Liquid Category 3		
GHS Hazard	Flammable liquid and vapour.; May cause an allergic skin reaction.; Suspected of causing		
Phrases:	cancer.; Very toxic to aquatic life.; Toxic to aquatic life with long lasting effects.		
GHS Precautions:			
Safety	Obtain special instructions before use. Do not handle until all safety precautions have been		
Precautions:	read and understood. Keep away from heat/sparks/open flames/hot surfaces No smoking.		
	Keep container tightly closed. Ground/bond container and receiving equipment. Use		
	explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools.		
	Take precautionary measures against static discharge. Avoid breathing		
	dust/fume/gas/mist/vapours/spray. Contaminated work clothing should not be allowed out		
	of the workplace. Avoid release to the environment. Wear protective gloves/protective		
	clothing/eye protection/face protection.		
First Aid	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin		
Measures:	with water/shower. IF exposed or concerned: Get medical advice/attention. Wash		
	contaminated clothing before reuse. In case of fire: Use water spray, foam, dry chemical or		
	carbon dioxide to extinguish. Collect spillage.		
Storage:	Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.		
Disposal:	Dispose of contents/container in accordance with local/regional/national/international		
	regulation for hazardous wastes.		



SAFETY DATA SHEET

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS #	PERCENT	Classification	Note
Stoddard solvent	8052-41-3	30 - 50	Asp. Tox. 1; H304	Note P
Titanium dioxide	13463-67-7	1 - 5	Carc. 2; H351	* (see below)
Zinc oxide	1314-13-2	1 - 5	Aquatic Acute 1; H400 Aquatic Chronic 1; H410	
Wood rosin	8050-09-7	0.1 - 1	Skin Sens. 1; H317	
Cumene	98-82-8	0.1 - 1	Aquatic Acute 1; H400 Aquatic Chronic 2; H411 Asp. Tox. 1; H304 Acute Tox. 4; H302 Carc. 2; H351 Flam. Liq. 3; H226 STOT SE 3; H335	
Antimony trioxide	1309-64-4	0.1 - 1	Aquatic Acute 1; H400 Carc. 2; H351	* (see below)
Tri(nonylphenol)phosphite	26523-78-4	0.1 - 1		
Hindered amine light stabilizer	41556-26-7	0.1 - 1		
Naphthalene	91-20-3	0.1 - 1	Aquatic Chronic 1; H410 Acute Tox. 2; H330 Acute Tox. 4; H302 Carc. 2; H351	
Ethylbenzene	100-41-4	0.1 - 1	Acute Tox. 4; H332 Acute Tox. 4; H332 Flam. Liq. 2; H225	
Decanedioic acid, methyl 1,2,2,6,6- pentamethyl-4-piperidinyl ester	82919-37-7	0.1 - 1	Aquatic Chronic 2; H411 Skin Sens. 1; H317	

*This product contains one or more materials that may be hazardous when present as an airborne dust. During normal handling of the product, the material is encapsulated within the product and will not present an exposure risk. Once the product has reached its final state and is abraded or disturbed, dusting and exposure may occur. This product contains titanium dioxide, which is hazardous when present as an airborne dust. As provided, and during normal use of this product, this substance is encapsulated within the product. As such, it is considered to be inextricably bound, and not readily available for exposure.

Unlisted ingredients are not 'hazardous' per the Occupational Safety and Health Administration Hazard Communication Standard (29 CFR 1910.1200) and/or are not found on the Canadian Workplace Hazardous Materials Information System ingredient disclosure list. See Section 8 for exposure limit guidelines.

SECTION 4: FIRST AID MEASURES

IF IN EYES: Flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention.

IF ON SKIN: Wash with soap and water. Remove contaminated clothing and launder. Get medical attention if irritation develops or persists.

IF INHALED: Remove to fresh air. Call a physician if symptoms persist.

IF SWALLOWED: Do not induce vomiting. Seek medical attention immediately. Drink two glasses of water or milk to dilute. Do not give anything by mouth to an unconscious person. Induced vomiting may lead to aspiration of the material into the lungs potentially causing chemical pneumonitis that may be fatal.



SAFETY DATA SHEET

SECTION 5: FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: UNUSUAL FIRE AND EXPLOSION HAZARDS:	Use water spray, foam, dry chemical or carbon dioxide. Vapors are heavier than air and can travel to a source of ignition and flash back.
SPECIAL FIRE FIGHTING INSTRUCTIONS:	Persons exposed to products of combustion should wear self- contained breathing apparatus and full protective equipment.
HAZARDOUS COMBUSTION PRODUCTS:	Carbon dioxide, Carbon monoxide Chlorine containing gases Metal fumes

SECTION 6: ACCIDENTAL RELEASE MEASURES

SPECIAL PROTECTION:	Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section 8 of this MSDS. Additional precautions may be necessary based on special circumstances created by the spill including; the material spilled, the
	quantity of the spill, the area in which the spill occurred. Evaporation of volatile substances can lead to the displacement of air creating an environment that can cause asphyxiation.
METHODS FOR CLEAN-UP:	Dike if necessary, contain spill with inert absorbent and transfer to containers for disposal. Keep spilled product out of sewers, watersheds, or water systems. Shut off ignition sources; including electrical equipment and flames. Do
Terror of Enterror of Discos New	not allow smoking in the area.

Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

SECTION 7: HANDLING AND STORAGE

Handling:	 Avoid contacting and avoid breathing the material. Use only in a well ventilated area. Keep away from heat, sparks and flame. Wash thoroughly after handling. Keep container closed. Emptied container retains vapor and product residue. Observe all labeled precautions until container is cleaned. Drums of this material should be grounded when pouring. DO NOT CUT OR WELD ON OR NEAR THIS CONTAINER.
Storage:	Store in a cool, dry, ventilated location. Keep away from heat and flame. Keep container closed.

Consult the Technical Data Sheet for specific storage instructions.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

EXPOSURE LIMITS:

Chemical Name	Note	ACGIH EXPOSURE LIMITS	OSHA PEL
Stoddard solvent	Note P	100 ppm TWA	500 ppm TWA; 2900 mg/m3 TWA
Talc, non-fibrous	* (see below)	2 mg/m3 TWA (particulate matter containing no asbestos and <1% crystalline silica, respirable fraction)	Not established



SAFETY DATA SHEET

Titanium dioxide	* (see below)	10 mg/m3 TWA	15 mg/m3 TWA (total dust)
Zinc oxide		2 mg/m3 TWA (respirable fraction) 10 mg/m3 STEL (respirable fraction)	5 mg/m3 TWA (fume); 15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)
Cumene		50 ppm TWA	50 ppm TWA; 245 mg/m3 TWA Skin absorption may potentially contribute to the overall exposure to this material.
Naphthalene		10 ppm TWA Skin absorption may potentially contribute to the overall exposure to this material.	10 ppm TWA; 50 mg/m3 TWA
Ethylbenzene		20 ppm TWA	100 ppm TWA; 435 mg/m3 TWA

*This product contains one or more materials that may be hazardous when present as an airborne dust. During normal handling of the product, the material is encapsulated within the product and will not present an exposure risk. Once the product has reached its final state and is abraded or disturbed, dusting and exposure may occur. This product contains titanium dioxide, which is hazardous when present as an airborne dust. As provided, and during normal use of this product, this substance is encapsulated within the product. As such, it is considered to be inextricably bound, and not readily available for exposure.

ENGINEERING CONTROL METHODS:

VENTILATION:	General room ventilation might be required under normal conditions of use.
EYE PROTECTION:	Wear safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid, or airborne material. Have an eye wash station available.
SKIN PROTECTION:	Avoid skin contact by wearing chemically resistant gloves and long sleeved shirt. An apron may be appropriate if splashing can occur. Skin absorption may potentially contribute to the overall exposure to this material. Appropriate measures should be taken to prevent absorption so that the TLV is not invalidated.
GLOVES:	Nitrile
RESPIRATORY PROTECTION:	No respiratory protection required under normal conditions of use. NIOSH approved air purifying respirator with organic vapor cartridge.
	Respirators should be selected by and used following requirements found in OSHA's respirator standard (29 CFR 1910.134).

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE:	Liquid
COLOR:	White
ODOR:	Mild Solvent
ODOR THRESHOLD:	Not established
pH:	Not established
FREEZING/MELTING POINT (deg. C):	Not established
BOILING POINT (deg. C):	Not established
FLASH POINT:	42°C; 108°F TCC
EVAPORATION RATE:	Not established
FLAMMABILITY:	Not a flammable solid or gas
UPPER EXPLOSIVE LIMIT (% in air):	Not established



Print Date: 01-09-2017

FOSTER 30-35 802256PM

SAFETY DATA SHEET

Not established Not established Not established 10.10 1.170 Not established Not established Not established Not established No data available. 61.3 Not determined 450g/liter of material

SECTION 10: STABILITY AND REACTIVITY

STABILITY: CHEMICAL INCOMPATIBILITY: HAZARDOUS POLYMERIZATION: HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide Chlorine

Stable under normal conditions. Strong oxidizing agents Will not occur. containing gases Metal fumes

SECTION 11: TOXICOLOGICAL INFORMATION

Component Toxicity / Toxicology Data:

COMPONENT NAME	LD50/LC50
Chlorinated paraffin	Oral LD50 Rat > 21,500 ML/KG

This product is a mixture. Unless noted, the information below is based on components.

Skin corrosion / irritation: No irritation hazard in normal industrial use.

Serious eye damage / irritation :No irritation hazard in normal industrial use.

Respiratory / skin sensitization: No data available.

Germ cell mutagenicity: No data available.

Carcinogenicity: Contains a material that is suspected of causing cancer.

Reproductive toxicity: No data available.

Specific target organ toxicity-single exposure: No data available.

Respiratory irritation / Narcotic effects: May cause respiratory irritation.

Specific target organ toxicity-repeated exposure: No data available.

Target organs potentially affected by exposure: Kidneys Central nervous system Lungs Skin Blood Liver

Aspiration hazard: Not an aspiration hazard.

Medical Conditions Aggravated by Exposure: Kidney disease, Lung disease, Skin disease including eczema and sensitization, Liver disease, Blood disorders (like anemia)

SECTION 12: ECOLOGICAL INFORMATION

OVERVIEW:

No ecological information available for this product.



SAFETY DATA SHEET

MOBILITY:	No data available.
PERSISTENCE:	No data available.
BIOACCUMULATION:	No data available.

This product has not been tested for ecological effects. Relevant information for components is listed below:

Component:	Ecotoxicity values:
Chlorinated paraffin	Acute Toxicity (Fish): 96 Hr LC50 Oncorhynchus mykiss: >0.0109 mg/L [flow-
_	through]; 96 Hr LC50 Oncorhynchus mykiss: 94.5 - 271 mg/L [static]; 96 Hr LC50
	Lepomis macrochirus: >0.1 mg/L [flow-through]
	Acute Toxicity (Daphnia): Not established
	Acute Toxicity (Algae): Not established

SECTION 13: DISPOSAL CONSIDERATIONS

This product meets the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. It is ignitable waste class D001. Disposal via incineration is recommended. Consult your state, local, or provincial authorities for more restrictive requirements.

LAND DISPOSAL RESTRICTIONS: Naphthalene ethylbenzene

SECTION 14: TRANSPORT INFORMATION

Consult Bill of Lading for transportation information.

US DOT:	UN1139, COATING SOLUTION, 3, III
IATA:	UN1139, COATING SOLUTION, 3, III
IMDG:	UN1139, COATING SOLUTION, 3, III, FLASH POINT 42°C C.C., EMS
	F-E, S-E

SECTION 15: REGULATORY INFORMATION

U.S. EPA TSCA:	This product is in compliance with the Toxic Substances Control Act's
	Inventory requirements.
CANADIAN CEPA DSL:	The components of this product are included on the DSL or are exempt
	from DSL requirements.
EUROPEAN REACH:	As a result of the introduction of REACH into Europe, this product
	cannot be imported into Europe unless the REACH requirements are
	met.
AUSTRALIA AICS:	This product is in compliance with the Australian Inventory of
	Chemical Substances requirements.
JAPAN ENCS:	This product is in compliance with the Japanese Existing and New
	Chemical Substances requirements.
KOREAN TCCL:	This product is in compliance with the Korean Existing Chemicals List
	requirements.
PHILIPPINES:	This product is in compliance with the Philippine Inventory of
	Chemicals and Chemical Substances requirements.
CHINA IECSC INVENTORY:	This product is in compliance with the Inventory of Existing Chemical
	Substances in China (IECSC) requirements.
TC	f the interaction status of this and heat call (51, 22) 5959

If you need more information about the inventory status of this product call 651-236-5858.

This product may contain chemical substances that are regulated for export by various government agencies (such as the Environmental Protection Agency, the Bureau of Industry and Security, or the Drug Enforcement



Page 7 of 8

FOSTER 30-35 802256PM

SAFETY DATA SHEET

Administration, among others). Before exporting this product from the USA or Canada, we recommend you contact us at reg.request@hbfuller.com to request an export review.

This product contains a chemical substance that is subject to a Significant New Use Rule (SNUR) under Section 5(a)(2) of TSCA:

4-Nonylphenol, branched

79 FR 59186, Oct 1, 2014 (Proposed rule)

FEDERAL REPORTING

*This product contains one or more materials that may be hazardous when present as an airborne dust. During normal handling of the product, the material is encapsulated within the product and will not present an exposure risk. Once the product has reached its final state and is abraded or disturbed, dusting and exposure may occur. This product contains titanium dioxide, which is hazardous when present as an airborne dust. As provided, and during normal use of this product, this substance is encapsulated within the product. As such, it is considered to be inextricably bound, and not readily available for exposure.

EPA SARA Title III Section 313

Unless listed below, this product does not contain toxic chemical(s) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR part 372. EPA has advised that when a percentage range is listed the midpoint may be used to fulfill reporting obligations.

Chemical Name	CAS#	%
Zinc compounds	1314-13-2	1 - 5
Cumene	98-82-8	0.1 - 1
Antimony compounds	1309-64-4	0.1 - 1
Naphthalene	91-20-3	0.1 - 1
ethylbenzene	100-41-4	0.1 - 1

STATE REPORTING

Proposition 65, The Safe Drinking Water and Toxic Enforcement Act of 1986:

Unless listed below, this product does not contain known levels of any chemical known to the State of California to cause cancer or reproductive harm.

Chemical Name/List		CAS	Percent
Titanium dioxide	(Carcinogen)	13463-67-7	1 - 5
Cumene	(Carcinogen)	98-82-8	0.1 - 1
Antimony(III) oxide	(Carcinogen)	1309-64-4	0.1 - 1
Naphthalene	(Carcinogen)	91-20-3	0.1 - 1
ethylbenzene	(Carcinogen)	100-41-4	0.1 - 1
Quartz	(Carcinogen)	14808-60-7	0.1 - 1
Benzene	(Carcinogen)	71-43-2	0.001 - 0.01
Lead compounds	(Carcinogen)		0.001 - 0.01
Arsenic compounds (inorganic)	(Carcinogen)		0.001 - 0.01
Lead	(Carcinogen)	7439-92-1	0.001 - 0.01
Cadmium	(Carcinogen)	7440-43-9	< 10 ppm
Benzene	(Developmental toxin)	71-43-2	0.001 - 0.01
Lead	(Developmental toxin)	7439-92-1	0.001 - 0.01
Cadmium	(Developmental toxin)	7440-43-9	< 10 ppm
Toluene	(Developmental toxin)	108-88-3	< 10 ppm
Lead	(Female reproductive toxin)	7439-92-1	0.001 - 0.01
Benzene, methyl-	(Female reproductive toxin)	108-88-3	< 10 ppm
Benzene	(Male reproductive toxin)	71-43-2	0.001 - 0.01
Lead	(Male reproductive toxin)	7439-92-1	0.001 - 0.01
Cadmium	(Male reproductive toxin)	7440-43-9	< 10 ppm

Substances of Very High Concern (SVHC) Content:

Unless listed below, this product does not contain SVHC's at 0.1% or greater, as of the version date of this SDS.



SAFETY DATA SHEET

SECTION 16: OTHER INFORMATION

SDS VERSION DATE: 09-26-2016

This Safety Data Sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200) and the Canadian Workplace Hazardous Materials Information System (WHMIS).

HMIS RATING: HEALTH -- 2 FLAMMABILITY -- 2 REACTIVITY -- 0 See SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for personal protective equipment recommendations.

Prepared by: The Global Regulatory Department Phone: 651-236-5842

The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to H.B. Fuller Construction Products, Inc. from its suppliers, and because H.B. Fuller Construction Products, Inc. has no control over the conditions of handling and use, H.B. Fuller Construction Products, Inc. makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and H.B. Fuller Construction Products, Inc. assumes no responsibility for use or reliance thereon. It is the responsibility of the user of H.B. Fuller Construction Products, Inc. products to comply with all applicable federal, state and local laws and regulations.