TECHLITE INSULATION

079 SERIES



079 SERIES

TechLite® 079 Series is a lightweight, open cell melamine foam insulation developed as an alternative to traditional insulation systems. This high performance insulation has a wide temperature range, low smoke and flame properties and is available in several sizes and shapes including preformed pipe insulation and fittings, flat sheets, die cut parts, and custom cut v-grooved sheets to wrap around large cylindrical surfaces. Custom shapes and profiles are available by request. TechLite® foam is easily trimmed, cut, and sliced in the field reducing installation time compared to many other insulation materials. In addition to providing excellent insulation properties, TechLite® Insulation also provides outstanding acoustical performance. 079 plain foam is also available with a variety of factory applied jacketing.

USES AND APPLICATIONS

Complete pipe/tube Insulation
Tanks and vessels
Noise reduction
Clean rooms
Sanitary/food processing

INSULATION SPECIFICATIONS	
INSULATION SPECIFICATIONS	
Insulation material	Open cell Melamine foam
Service temperature	-40°F to 350°F
Thermal conductivity, k	0.27 BTU•in/hr•ft²•°F
Density	$0.44 \pm 0.19 \text{ lb/ft}^3$
Flame spread/smoke development	25/50 per ASTM E84
Color	Charcoal
Standard thickness	1", 1½", 2", 2½", 3"

Rev A October 2017