



**Midwest Fasteners**  
450 Richard St.  
Miamisburg, OH 45342  
**Website:** [www.midwestfasteners.com](http://www.midwestfasteners.com)  
**Email:** [sales@midwestfasteners.com](mailto:sales@midwestfasteners.com)

**Toll Free:** (800) 852-8352  
**Phone:** (937) 866-0463  
**Fax:** (937) 866-4174

[All Categories](#) > [Insulation Fasteners](#) > [Capacitor Discharge Weld Pins & Arc Weld Pins](#) > [J-Hook \(Weld Pin\)](#)

## J-HOOK (WELD PIN)

Size	D*	L
10GA	0.135	AS REQUIRED

\*Other diameters available upon request.

### **Materials**

#### **Low Carbon Steel**

C - 0.23% max. P - 0.04% max.

Mn - 0.90% max. S - 0.05% max.

#### **Stainless Steel**

AISI grade - 302/304/305 std.

Other grades available upon request.

### **Mechanical Properties**

#### **Low Carbon Steel**

Tensile - 60,000 psi (min.)

Yield - 50,000 psi (min.)

Elongation - 20% (in 2 inches)

#### **Stainless Steel**

Values for various grades available upon request.

### **Plating**

Galvanized and Copper plating are available for Low Carbon Steel

### **Annealing**

Low Carbon Steel can be annealed where required.

### **Washers**

Self-locking washers are available in a variety of sizes, shapes, and materials.

### **Application**

This is the standard insulation fastener used to secure insulation to wire road mesh.

Please click the [Request Information](#) button to configure your J-Hook (Weld Pin).

[less](#)

