

**SAFETY DATA SHEET**

REVISION DATE: 01-03-2020

SUPERSEDES: 10-27-2015

**SECTION 1: IDENTIFICATION OF THE PRODUCT AND SUPPLIER****PRODUCT INFORMATION**

PRODUCT: CHILDERS CP-30 LO  
PRODUCT DESCRIPTION: Coating  
INTENDED USE: Coating  
PRODUCT IDENTIFIER: 801811PM


**COMPANY INFORMATION**

H.B. Fuller Construction Products Inc.  
1105 S. Frontenac Street  
Aurora, IL 60504  
Phone: 1-800-552-6225

Medical Emergency Phone Number (24 Hours): 1-888-853-1758  
Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

**SECTION 2: HAZARDS IDENTIFICATION**

**GHS Hazard Symbols:**



**GHS Signal Word:** Warning

**GHS Classification:** Skin Sensitisation Category 1; Carcinogenicity Category 2; Hazardous to the aquatic environment - Chronic Category 2; Flammable Liquid Category 3; Hazardous to the aquatic environment - Acute Category 3; Additional category for effects on or via lactation Flammable liquid and vapour.; May cause an allergic skin reaction.; Suspected of causing cancer.; May cause harm to breast-fed children.; Harmful to aquatic life.; Toxic to aquatic life with long lasting effects.

**GHS Hazard Phrases:**

**GHS Precautions:**

**Safety Precautions:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact during pregnancy/while nursing. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.

**First Aid Measures:** IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. IF exposed or concerned: Get medical advice/attention. Wash contaminated clothing before reuse. In case of fire: Use water spray, foam, dry chemical or carbon dioxide to extinguish. Collect spillage.

**Storage:** Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.

**Disposal:** Dispose of contents/container in accordance with local/regional/national/international regulation for chemical wastes.

**SAFETY DATA SHEET**

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical Name	CAS #	PERCENT	Classification	Note
Stoddard solvent	8052-41-3	30 - 50	Asp. Tox. 1; H304	Note P
Calcium sulfate	7778-18-9	10 - 30		* (see below)
Titanium dioxide	13463-67-7	1 - 5	Carc. 2; H351	* (see below)
Cumene	98-82-8	0.1 - 1	Aquatic Chronic 2; H411 Asp. Tox. 1; H304 Acute Tox. 4; H302 Carc. 2; H351 Flam. Liq. 3; H226 STOT SE 3; H335, H336	
Antimony trioxide	1309-64-4	0.1 - 1	Carc. 2; H351	* (see below)
Tri(nonylphenol)phosphite	26523-78-4	0.1 - 1	Aquatic Chronic 1; H410 Skin Sens. 1; H317	
Naphthalene	91-20-3	0.1 - 1	Aquatic Acute 1; H400 Aquatic Chronic 1; H410 Acute Tox. 2; H330 Acute Tox. 4; H302 Carc. 2; H351	
Ethylbenzene	100-41-4	0.1 - 1	Asp. Tox. 1; H304 Acute Tox. 4; H332 Carc. 2; H351 Flam. Liq. 2; H225 STOT RE 2; H373	

\*This product contains one or more materials that may be hazardous when present as an airborne dust. During normal handling of the product, the material is encapsulated within the product and will not present an exposure risk. Once the product has reached its final state and is abraded or disturbed, dusting and exposure may occur. This product contains titanium dioxide, which is hazardous when present as an airborne dust. As provided, and during normal use of this product, this substance is encapsulated within the product. As such, it is considered to be inextricably bound, and not readily available for exposure.

Unlisted ingredients are not 'hazardous' per the Occupational Safety and Health Administration Hazard Communication Standard (29CFR 1910.1200) and/or are not found on the Canadian Workplace Hazardous Materials Information System ingredient disclosure list. See Section 8 for exposure limit guidelines.

**SECTION 4: FIRST AID MEASURES**

**IF IN EYES:** Flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention.

**IF ON SKIN:** Wash with soap and water. Remove contaminated clothing and launder. Get medical attention if irritation develops or persists.

**IF INHALED:** Remove to fresh air. Restore breathing, if necessary. Call a physician if symptoms persist.

**IF SWALLOWED:** Do not induce vomiting. Seek medical attention immediately. Drink two glasses of water or milk to dilute. Do not give anything by mouth to an unconscious person. Induced vomiting may lead to aspiration of the material into the lungs potentially causing chemical pneumonitis that may be fatal.

**SECTION 5: FIRE FIGHTING MEASURES**

**EXTINGUISHING MEDIA:**

Use water spray, foam, dry chemical or carbon dioxide.

**UNUSUAL FIRE AND EXPLOSION HAZARDS:**

Vapors are heavier than air and can travel to a source of ignition

**SAFETY DATA SHEET**

SPECIAL FIRE FIGHTING INSTRUCTIONS: and flash back.  
Persons exposed to products of combustion should wear self-contained breathing apparatus and full protective equipment.

HAZARDOUS COMBUSTION PRODUCTS: Carbon dioxide, Carbon monoxide Sulfur containing gases  
Chlorine containing gases

**SECTION 6: ACCIDENTAL RELEASE MEASURES**

SPECIAL PROTECTION: Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section 8 of this MSDS. Additional precautions may be necessary based on special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred. Evaporation of volatile substances can lead to the displacement of air creating an environment that can cause asphyxiation.

METHODS FOR CLEAN-UP: Dike if necessary, contain spill with inert absorbent and transfer to containers for disposal. Keep spilled product out of sewers, watersheds, or water systems.  
Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area.

Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

**SECTION 7: HANDLING AND STORAGE**

Handling: A void contacting and avoid breathing the material. Use only in a well ventilated area.  
Keep away from heat, sparks and flame.  
Wash thoroughly after handling.  
Keep container closed.  
Emptied container retains vapor and product residue.  
Observe all labeled precautions until container is cleaned.  
Drums of this material should be grounded when pouring.  
**DO NOT CUT OR WELD ON OR NEAR THIS CONTAINER.**

Storage: Store in a cool, dry, ventilated location. Keep away from heat and flame. Keep container closed.

Consult the Technical Data Sheet for specific storage instructions.

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

**EXPOSURE LIMITS:**

Chemical Name	Note	ACGIH EXPOSURE LIMITS	OSHA PEL
Stoddard solvent	Note P	100 ppm TWA	500 ppm TWA; 2900 mg/m3 TWA
Calcium sulfate	* (see below)	10 mg/m3 TWA (inhalable particulate matter)	15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)
Talc, non-fibrous	* (see below)	2 mg/m3 TWA (particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter)	Not established
Titanium dioxide	* (see below)	10 mg/m3 TWA	15 mg/m3 TWA (total dust)

**SAFETY DATA SHEET**

Trimethyl benzene		25 ppm TWA	Not established
Cumene		50 ppm TWA	50 ppm TWA; 245 mg/m <sup>3</sup> TWA Skin absorption may potentially contribute to the overall exposure to this material.
Naphthalene		10 ppm TWA Skin absorption may potentially contribute to the overall exposure to this material.	10 ppm TWA; 50 mg/m <sup>3</sup> TWA
Ethylbenzene		20 ppm TWA	100 ppm TWA; 435 mg/m <sup>3</sup> TWA

\*This product contains one or more materials that may be hazardous when present as an airborne dust. During normal handling of the product, the material is encapsulated within the product and will not present an exposure risk. Once the product has reached its final state and is abraded or disturbed, dusting and exposure may occur. This product contains titanium dioxide, which is hazardous when present as an airborne dust. As provided, and during normal use of this product, this substance is encapsulated within the product. As such, it is considered to be inextricably bound, and not readily available for exposure.

**ENGINEERING CONTROL METHODS:**

- VENTILATION:** Use local exhaust ventilation or other engineering controls to minimize exposures.
- EYE PROTECTION:** Wear safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid, or airborne material. Have an eye wash station available.
- SKIN PROTECTION:** Avoid skin contact by wearing chemically resistant gloves and long sleeved shirt. An apron may be appropriate if splashing can occur. Skin absorption may potentially contribute to the overall exposure to this material. Appropriate measures should be taken to prevent absorption so that the TLV is not invalidated.
- GLOVES:** Nitrile
- RESPIRATORY PROTECTION:** Respiratory protection may be required to avoid overexposure when handling this product. Use a respirator if general room ventilation is not available or sufficient to eliminate symptoms. NIOSH approved air purifying respirator with organic vapor cartridge. Respirators should be selected by and used following requirements found in OSHA's respirator standard (29 CFR 1910.134).

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

PHYSICAL STATE:	Liquid
COLOR:	White
ODOR:	Solvent Mild
ODOR THRESHOLD:	Not established
pH:	Not established
FREEZING/MELTING POINT (deg. C):	Not established
BOILING POINT (deg. C):	Not established
FLASH POINT:	42°C; 108°F TCC
EVAPORATION RATE:	Not established
FLAMMABILITY:	Not a flammable solid or gas
UPPER EXPLOSIVE LIMIT (% in air):	Not established
LOWER EXPLOSIVE LIMIT (% in air):	Not established
VAPOR PRESSURE (mm Hg):	Not established
VAPOR DENSITY:	Not established

**SAFETY DATA SHEET**

WEIGHT PER GALLON (lbs.):	9.60
SPECIFIC GRAVITY:	1.150
SOLUBILITY:	Not established
OCTANOL/WATER COEFFICIENT:	Not established
AUTOIGNITION TEMPERATURE:	Not established
DECOMPOSITION TEMPERATURE:	Not established
VISCOSITY:	No data available.
SOLIDS (% by weight):	57.0
VOC, weight percent	40.89
VOC, U.S. EPA Method 24, less water and exempt solvents (theoretically determined)	469g/liter of material

**SECTION 10: STABILITY AND REACTIVITY**

STABILITY:	Stable under normal conditions.
CHEMICAL INCOMPATIBILITY:	Strong oxidizing agents
HAZARDOUS POLYMERIZATION:	Will not occur.
HAZARDOUS DECOMPOSITION PRODUCTS:	Carbon monoxide, carbon dioxide Sulfur containing gases Chlorine containing gases

**SECTION 11: TOXICOLOGICAL INFORMATION**

**Component Toxicity / Toxicology Data:**

COMPONENT NAME	LD50/LC50
Chlorinated paraffin	Oral LD50 Rat > 21,500 microliter/kg
Chlorinated paraffin	Oral LD50 Rat > 21,500 microliter/kg
Trimethyl benzene	Oral LD50 Rat 8,970 mg/kg
Trimethylbenzene, 1,2,4-	Oral LD50 Rat 3,280 mg/kg Inhalation LC50 Rat 18.00 G/M3 Dermal LD50 Rabbit > 3,160.00 mg/kg

**This product is a mixture. Unless noted, the information below is based on components.**

Skin corrosion/ irritation: No irritation hazard in normal industrial use.

Serious eye damage / irritation :No irritation hazard in normal industrial use.

Respiratory / skin sensitization: No data available.

Germ cell mutagenicity: No data available.

Carcinogenicity: Contains a material that is suspected of causing cancer.

Reproductive toxicity: No data available.

Specific target organ toxicity-single exposure: No data available.

Respiratory irritation / Narcotic effects: No data available.

Specific target organ toxicity-repeated exposure: No data available.

Target organs potentially affected by exposure: Kidneys Central nervous system Lungs Blood Liver

Aspiration hazard: Not an aspiration hazard.

Medical Conditions Aggravated by Exposure: Kidney disease, Lung disease, Blood disorders (like anemia), Liver disease

**SAFETY DATA SHEET**

**SECTION 12: ECOLOGICAL INFORMATION**

OVERVIEW: No ecological information available for this product.  
 MOBILITY: No data available.  
 PERSISTENCE: No data available.  
 BIOACCUMULATION: No data available.

**This product has not been tested for ecological effects. Relevant information for components is listed below:**

Component:	Ecotoxicity values:
Chlorinated paraffin	<b>Acute Toxicity (Fish):</b> 96 Hr LC50 Oncorhynchus mykiss: >0.0109 mg/L [flow-through]; 96 Hr LC50 Oncorhynchus mykiss: 94.5 - 271 mg/L [static]; 96 Hr LC50 Lepomis macrochirus: >0.1 mg/L [flow-through] <b>Acute Toxicity (Daphnia):</b> Not established <b>Acute Toxicity (Algae):</b> Not established
Chlorinated paraffin	<b>Acute Toxicity (Fish):</b> 96 Hr LC50 Oncorhynchus mykiss: >0.0109 mg/L [flow-through]; 96 Hr LC50 Oncorhynchus mykiss: 94.5 - 271 mg/L [static]; 96 Hr LC50 Lepomis macrochirus: >0.1 mg/L [flow-through] <b>Acute Toxicity (Daphnia):</b> Not established <b>Acute Toxicity (Algae):</b> Not established
Trimethyl benzene	<b>Acute Toxicity (Fish):</b> LC50 96 h Pimephales promelas 7.72 mg/L [flow-through] <b>Acute Toxicity (Daphnia):</b> Not established <b>Acute Toxicity (Algae):</b> Not established
Trimethylbenzene, 1,2,4-	<b>Acute Toxicity (Fish):</b> LC50 96 h Pimephales promelas 7.19 - 8.28 mg/L [flow-through] (EPA) <b>Acute Toxicity (Daphnia):</b> EC50 48 h Daphnia magna 6.14 mg/L (IUCLID) <b>Acute Toxicity (Algae):</b> Not established

**SECTION 13: DISPOSAL CONSIDERATIONS**

This product meets the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. It is ignitable waste class D001. Disposal via incineration is recommended. Consult your state, local, or provincial authorities for more restrictive requirements.

LAND DISPOSAL RESTRICTIONS: Naphthalene ethylbenzene

**SECTION 14: TRANSPORT INFORMATION**

Consult Bill of Lading for transportation information.

US DOT: UN1139, COATING SOLUTION, 3, III  
 IATA: UN1139, COATING SOLUTION, 3, III  
 IMDG: COATING SOLUTION, 3, UN1139, III, FLASH POINT 38°C C.C., EMS F-E, S-D

**SECTION 15: REGULATORY INFORMATION**

**INVENTORY STATUS**

U.S. EPA TSCA: This product is in compliance with the Toxic Substances Control Act's Inventory requirements.  
 CANADIAN CEPA DSL: The components of this product are included on the DSL or are exempt from DSL requirements.  
 EUROPEAN REACH: As a result of the introduction of REACH into Europe, this product cannot be imported into Europe unless the REACH requirements are met.  
 AUSTRALIA AICS: This product is in compliance with the Australian Inventory of Chemical Substances requirements.

**SAFETY DATA SHEET**

If you need more information about the inventory status of this product call 651-236-5858.

This product may contain chemical substances that are regulated for export by various government agencies (such as the Environmental Protection Agency, the Bureau of Industry and Security, or the Drug Enforcement Administration, among others). Before exporting this product from the USA or Canada, we recommend you contact us at [reg.request@hbfuller.com](mailto:reg.request@hbfuller.com) to request an export review.

This product contains a chemical substance that is subject to a Significant New Use Rule (SNUR) under Section 5(a)(2) of TSCA:

Alkanes, C22-30-branched and linear, chloro  
4-Nonylphenol, branched  
  
40 CFR 721.10674 (PMNP-13-0107)  
79 FR 59186, Oct 1, 2014 (proposed rule)

**FEDERAL REPORTING**

\*This product contains one or more materials that may be hazardous when present as an airborne dust. During normal handling of the product, the material is encapsulated within the product and will not present an exposure risk. Once the product has reached its final state and is abraded or disturbed, dusting and exposure may occur. This product contains titanium dioxide, which is hazardous when present as an airborne dust. As provided, and during normal use of this product, this substance is encapsulated within the product. As such, it is considered to be inextricably bound, and not readily available for exposure.

**EPA SARA Title III Section 313**

Unless listed below, this product does not contain toxic chemical(s) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR part 372. EPA has advised that when a percentage range is listed the midpoint may be used to fulfill reporting obligations.

Chemical Name	CAS#	%
1,2,4-Trimethylbenzene	95-63-6	1 - 5
Cumene	98-82-8	0.1 - 1
Antimony compounds	1309-64-4	0.1 - 1
Naphthalene	91-20-3	0.1 - 1
ethylbenzene	100-41-4	0.1 - 1

**STATE REPORTING**

Proposition 65, The Safe Drinking Water and Toxic Enforcement Act of 1986:

Unless listed below, this product does not contain known levels of any chemical known to the State of California to cause cancer or reproductive harm.

Chemical Name/List	CAS	Percent
Titanium dioxide (Carcinogen)	13463-67-7	1 - 5
Cumene (Carcinogen)	98-82-8	0.1 - 1
Antimony(III) oxide (Carcinogen)	1309-64-4	0.1 - 1
Naphthalene (Carcinogen)	91-20-3	0.1 - 1
ethylbenzene (Carcinogen)	100-41-4	0.1 - 1
Quartz (Carcinogen)	14808-60-7	0.1 - 1
Benzene (Carcinogen)	71-43-2	0.001 - 0.01
Lead compounds (Carcinogen)		0.001 - 0.01
Arsenic compounds (inorganic) (Carcinogen)		0.001 - 0.01
Lead (Carcinogen)	7439-92-1	< 10 ppm
Cadmium (Carcinogen)	7440-43-9	< 10 ppm
Benzene (Developmental toxin)	71-43-2	0.001 - 0.01
Toluene (Developmental toxin)	108-88-3	< 10 ppm
Lead (Developmental toxin)	7439-92-1	< 10 ppm
Cadmium (Developmental toxin)	7440-43-9	< 10 ppm
Benzene, methyl- (Female reproductive toxin)	108-88-3	< 10 ppm
Lead (Female reproductive toxin)	7439-92-1	< 10 ppm
Benzene (Male reproductive toxin)	71-43-2	0.001 - 0.01
Lead (Male reproductive toxin)	7439-92-1	< 10 ppm

**SAFETY DATA SHEET**

Cadmium	(Male reproductive toxin)	7440-43-9	< 10 ppm
---------	---------------------------	-----------	----------

**Substances of Very High Concern (SVHC) Content:**

Unless listed below, this product does not contain SVHC's at 0.1% or greater, as of the version date of this SDS.

**SECTION 16: OTHER INFORMATION**

SDS VERSION DATE: 01-03-2020

This Safety Data Sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200) and the Canadian Workplace Hazardous Materials Information System (WHMIS).

HMIS RATING: HEALTH -- 2 FLAMMABILITY -- 2 REACTIVITY -- 0

See SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for personal protective equipment recommendations.

Prepared by: The Global Regulatory Department

Phone: 651-236-5842

The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to H.B. Fuller Construction Products, Inc. from its suppliers, and because H.B. Fuller Construction Products, Inc. has no control over the conditions of handling and use, H.B. Fuller Construction Products, Inc. makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and H.B. Fuller Construction Products, Inc. assumes no responsibility for use or reliance thereon. It is the responsibility of the user of H.B. Fuller Construction Products, Inc. products to comply with all applicable federal, state and local laws and regulations.