

SPECIFICATIONS

GLT Products stocks four styles of fiberglass resin coated scrim designed for use with tar or asphalt based waterproofing compounds. Scrim cloth is ideal for use with mastics and coatings on insulated indoor, outdoor and underground piping, tanks and other mechanical equipment.

ADVANTAGES:

Glass Fabric Base:

- Extremely high tensile strength
- Dimensionally stable
- Will not burn, rot, mildew or decay
- Contour flexibility without cracking
- Acid and alkali resistance

Resinous Coating:

- Free of tackiness
- Unaffected by hot storage
- Unrolls easily and uniformly
- Clean and neat to handle
- Colors permit emulsion match or contrast
- Federal and other code compliance



Specifications:

- Meets ASTM-D-1668-80, Part 15, specifications for woven glass fabrics treated for use in waterproofing and roofing, Type III
- Also available as slit tapes

Style	Weave Size (Sq. In.)	Available Colors	Roll Size	Thickness (inch)	Weight/Sq. Yd. (oz.)	Break Strength (lb./in.)
GS37	6 x 6	White	38" x 150'	0.010	3.97	150 x 155
GS1620	20 x 20	White	36" x 150'	0.002	1.60	80 x 70
GS1659	10 x 10	White White White White or Black White	2" x 150' 3" x 150' 4" x 150' 36" x 150' 48" x 150'	0.0042	1.64	65 x 70
GS1659-PSA	10 x 10	White	2" x 150' 3" x 150' 4" x 150' 6" x 150' 36" x 150'	.0042	1.64	65 x 70