

TECHNICAL INFO

Manufactured of 100% fiberglass yarn to ensure flame retardancy, insulating protection and durability. Resistant to high temperatures and is easy to handle, cut and sew.

Properties:

Thread Count: 56 × 54

Weight (oz/sq yd): 9.43

Thickness (inches): 0.0009"

Breaking Strength (warp): 200 lb. minimum

Meets Military Specification MIL-C020079 Type 1 Class 1

Meets Military Specification MIL-I-24244

Width: 38" and 50"

Also available in narrow tapes – 2", 3" and 4"



All statements herein are expressions of opinion, which we believe to be accurate and reliable, but are presented without guarantee or responsibility on our part. Anyone intending to use recommendations contained in this publication concerning equipment, processing techniques or products should first satisfy himself that the recommendations are suitable for his use and meet all appropriate safety and health standards.

For more information on GLT Products, please call toll-free at 800.874.1748 or online at www.gltproducts.com.



Innovative Insulation Systems

HEADQUARTERS:

6810 Cochran Road | Solon OH 44139 | 440.914.1122 | 440.914.1133 Fax | **1.800.874.1748**

DISTRIBUTION CENTERS:

Ohio: 6810 Cochran Road | Solon OH 44139 | 440.914.1122

North Carolina: 501 West Camel Street | Greensboro, NC 27401 | 1.800.551.9760

California: 4113 Gold River Lane | Stockton, CA 95215 | 1.800.833.4500

Texas: 8905 Market Street | Houston, TX 77029 | 1.800.874.1748