



Midwest Fasteners
 450 Richard St.
 Miamisburg, OH 45342
 Website: www.midwestfasteners.com

Toll Free: (800) 852-8352
Phone: (937) 866-0463
Fax: (937) 866-4174
Email: sales@midwestfasteners.com

[All Categories](#) > [Insulation Fasteners](#) > [Insulation Fastener Washers, Caps & Nuts](#) > [Self-Locking Washers \(Square\)](#)

SELF-LOCKING WASHERS (SQUARE)

Type	K250	K150	K125
Diameter	2-1/2 x 2-1/2	1-1/2 x 1-1/2	1-1/4 x 1-1/8
Thickness	0.015 nom.	0.015 nom.	0.015 nom
Material	Mild Steel	Mild Steel	Mild Steel
Plating	Galv.	Galv.	Galv.
Edges / flat or beveled	beveled	beveled	beveled
Other materials available	Alum., S.S.	Alum., S.S.	Alum., S.S.
Packaged per carton	1000	1000	1000

MIDWEST FASTENERS Self-Locking Washers are used in conjunction with MIDWEST FASTENERS weld pins, insul-anchors and lacing anchors to fasten insulation in place. Simply press the self-locking washer onto the pin up to the insulation until the desired position is reached. Then clip off, (or bend over) the remaining portion of pin for a permanent attachment.

Both Round or Square self-locking washers are available as a matter of design or application preference. The domed, multi-lanced hole design provides for ease of locating washer on pin and positive locking. Most styles of washers are manufactured with a beveled edge to prevent the washer from cutting into the insulation facing.

MIDWEST FASTENERS Self-Locking Washers are available according to the chart above and with standard 10 GA, 3mm, 12 GA, or 14 GA hole sizes off-the-shelf. Other material/plating combinations and hole sizes are available by special order.

Please click the [Request Information](#) button to configure your Self-Locking Washers (Square).

[less](#)

Self-Locking Washers

