

# DYPLAST PRODUCTS

## UNFACED RIGID POLYISOCYANURATE FOAM

### SAFETY DATA SHEET

DYPLAST PRODUCTS, LLC 12501 NW 38TH AVENUE MIAMI, FLORIDA 33054

*IMPORTANT: Read this SDS before handling and disposing of this product and pass this information on to employees, customers, and users of this product. This product is covered by the OSHA Hazard Communication Rule and this document has been prepared in accordance with the SDS requirements of the rule.*

#### SECTION 1: IDENTIFICATION

**Trade Name:** ISO-HT (density 2.5 lb/ft<sup>3</sup>)  
**Telephone Number:** (305) 921-0100 MIAMI, FL  
**Other Names:** UNFACED ISO, POLYISO  
**Chemical Name/Family:** POLYISOCYANURATE RIGID FOAM INSULATION  
**DOT Hazardous Materials**  
**Proper Shipping Name:** NOT REGULATED (SEE SUPPLEMENT)  
**Generic Name:** POLYISOCYANURATE  
**DOT Hazard Class:** NOT REGULATED  
**CAS No:** PROPRIETARY  
**Amount:** 100%  
**PEL/TLV:** NOT ESTABLISHED

#### SECTION 2: HAZARDS IDENTIFICATION

**Acute Health Effects (Short-Term):** CAN BE A MECHANICAL IRRITANT TO SKIN, EYES, & UPPER RESPIRATORY SYSTEM DURING FABRICATION  
**Chronic Health Effects (Long-Term):** STUDIES SHOW NO STATISTICALLY SIGNIFICANT INCREASED RISK OF RESPIRATORY DISEASES  
**Inhalation:** Dust may cause irritation to the upper respiratory tract (nose and throat). NO SIGNIFICANT SIGNS OR SYMPTOMS INDICATIVE OF ANY ADVERSE HEALTH ARE EXPECTED TO OCCUR AS A RESULT OF INHALATION EXPOSURE.  
**Eye Contact:** MAY CAUSE MINOR EYE IRRITATION FROM DUST ORIGINATING FROM FABRICATION.  
**Skin Absorption:** NO SIGNIFICANT SIGNS OR SYMPTOMS INDICATIVE OF ANY ADVERSE HEALTH HAZARD ARE EXPECTED TO OCCUR AS A RESULT OF SKIN ABSORPTION.  
**Skin Irritation:** MAY PRODUCE SLIGHT SKIN IRRITATION.  
**Ingestion:** NO SIGNIFICANT SIGNS OR SYMPTOMS INDICATIVE OF ANY ADVERSE HEALTH HAZARD ARE EXPECTED TO OCCUR AS A RESULT OF INGESTION. PRODUCT IS NOT FOR CONSUMPTION.  
**Summary Chronic Hazards and Special Health Effects:** THE MAJOR COMPONENTS OF THIS PRODUCT HAVE NOT BEEN IDENTIFIED AS SIGNIFICANT HAZARDS IN LONGTERM STUDIES.  
**Hazardous Decomposition Products (Fire):** LIKE WOOD AND OTHER ORGANIC MATERIALS CAN RELEASE TOXIC SMOKE IF IGNITED.

NO ADDITIONAL MEDICAL INFORMATION FOUND.

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

*(This may not be a complete list of components)*

Component Name	(%)	CAS #
Modified polyisocyanurate polymer	≥85	Not applicable
Cyclopentane	<5	287-92-3
Isopentane	<5	78-78-4
Tris (1-chloro-2-propyl) phosphate	≤5	13674-84-5

### SECTION 4: FIRST AID MEASURES

**Inhalation:** REMOVE TO FRESH AIR.

**Eye Contact:** FLUSH WITH WATER FOR 15-20 MINUTES OR UNTIL IRRITATION CEASES.

**Skin Contact:** WASH WITH SOAP AND WATER.

**Ingestion:** IF SWALLOWED, DILUTE WITH WATER. DO NOT INDUCE VOMITING.

**Emergency Medical Treatment Procedures:** PERSONS WHO DEVELOP SYMPTOMS OF ALLERGY, IRRITATION, RESPIRATORY PROBLEMS, OR PUFFINESS AROUND THE EYES SHOULD BE EXAMINED BY A PHYSICIAN AS SOON AS POSSIBLE.

### SECTION 5: FIRE FIGHTING MEASURES

**Flash Point (Method):** UNKNOWN

**Auto-ignition Temperature:** Greater than 450°C, per ASTM D1929

**Flammable Limits (% Vol. in Air)**

**At Normal Atmospheric Temperature and Pressure:** Lower: N/A Upper: N/A

**Fire and Explosion Hazards:** POLYISOCYANURATE FOAM WILL BURN IF EXPOSED TO FLAME OF SUFFICIENT HEAT AND INTENSITY. LIKE OTHER ORGANIC MATERIALS, CAN RELEASE TOXIC SMOKE IF IGNITED.

**Extinguishing Media:** DRY CHEMICAL, CO<sub>2</sub>, WATER SPRAY, WATER FOG, FOAM, WATER

**Special Firefighting Procedures:** SELF-CONTAINED BREATHING APPARATUS, dense smoke is emitted when polyisocyanurate foam is burned in an oxygen starved environment.

**Unusual Fire Hazards:** Cutting, grinding and sawing can cause the formation of dust. To reduce the potential of dust explosions, do not permit dust to accumulate, provide adequate ventilation and practice good housekeeping procedures.

The compaction of polyisocyanurate foam for disposal can entrap pentane in pockets of the compressed foam or at the bottom of the compactor. Appropriate engineering of the compactor is recommended to keep pentane levels below the LFL levels and to remove potential ignition sources caused from metal to metal contact in the compactor.

**SECTION 6: ACCIDENTAL RELEASE MEASURES**

**Precautions If Material is Spilled or Released:** NOT APPLICABLE

**Waste Disposal Methods:** DISPOSAL SHOULD BE IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL REGULATIONS.

**SECTION 7: HANDLING AND STORAGE**

PROTECT FROM MOISTURE. WHEN STORED OUTDOORS, STACK ABOVE GROUND LEVEL AND COVER WITH TARPAULINS OR OTHER SUITABLE COVERING.

THIS MATERIAL IS COMBUSTIBLE AND SHOULD NOT BE EXPOSED TO FLAME OR OTHER IGNITION SOURCES, REFER TO FIRE AND EXPLOSION RISKS (SECTION 5 IN THIS SDS).

THE ACGIH LISTING FOR HYDROCARBON BLOWING AGENTS HAVE A TIME WEIGHTED AVERAGE OF 600 PPM.

NO SMOKING, OPEN FLAMES, OR SOURCES OF IGNITION IN HANDLING AND STORAGE AREA.

FABRICATION METHODS WHICH INVOLVE CUTTING INTO THIS PRODUCT MAY RELEASE THE BLOWING AGENT REMAINING IN THE DAMAGED CELLS. PROVIDE ADEQUATE VENTILATION TO ASSURE LOCALIZED CONCENTRATIONS OF THE BLOWING AGENT ARE MAINTAINED BELOW THE LFL (LOWER FLAMMABILITY LIMIT)

**Shipping Regulations:** NOT CLASSIFIED AS A HAZARDOUS MATERIAL BY DEPARTMENT OF TRANSPORTATION DEFINITIONS AND HENCE IT IS NOT REGULATED.

**Materials to Avoid:** DIRECT APPLICATION OF HOT ASPHALT.

**Conditions to Avoid:** AVOID TEMPERATURES ABOVE 150°C (302°F) DURING STORAGE. EXPOSURE TO ELEVATED TEMPERATURES CAN CAUSE PRODUCT TO DECOMPOSE. AVOID DIRECT SUNLIGHT. AVOID OPEN FLAME OR OTHER IGNITION SOURCES AND PROLONGED EXPOSURE TO THE ELEMENTS.

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

Substance	Source	Date	Type	Value/Units	Time
NUISANCE DUST (TOTALS)	OSHA	1989	TWA	15 MG/MS	8 HRS
NUISANCE PARTICULATES	ACGIH	1989	TWA	10 MG/M3	8 HRS
NUISANCE DUST (RESP.)	OSHA	1989	TWA	5 MG/M3	8 HRS

**Respiratory:** USE NIOSH/OSHA APPROVED PARTICULATE FILTER MASK DURING FABRICATION.  
**Eye:** WEAR SAFETY GLASSES OR GOGGLES.  
**Skin:** NOT NORMALLY CONSIDERED A SKIN HAZARD. PRACTICE GOOD PERSONAL HYGIENE.  
**Engineering Controls:** EXERCISE GOOD HOUSEKEEPING PROCEDURES. REMOVE DUST DURING FABRICATION BY VACUUM.  
**Other Hygienic and Work Practices:** PROVIDE ADEQUATE VENTILATION WHEN FABRICATING. REMOVE DUST PROMPTLY.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

**Appearance and Odor:** RIGID TAN CELLULAR PLASTIC. NO ODOR.  
**Flammability Limits:** At Normal Atmospheric Temperature and Pressure: Lower: N/A Upper: N/A  
**Odor:** Odorless  
**Vapor Pressure:** NOT APPLICABLE  
**Odor Threshold:** NOT APPLICABLE  
**Vapor Density:** NOT APPLICABLE  
**Vapor Specific Gravity:** NOT APPLICABLE  
**Boiling Point:** NOT APPLICABLE  
**pH:** NOT APPLICABLE  
**Relative Density:** NOT APPLICABLE  
**Specific Gravity:** NOT APPLICABLE  
**Melting Point:** NOT APPLICABLE  
**Freezing Point:** NOT APPLICABLE  
**Solubility in Water:** NOT APPLICABLE  
**Initial Boiling Point and Boiling Range:** NOT APPLICABLE  
**Flash Point:** NOT APPLICABLE  
**Evaporation Rate:** NOT APPLICABLE  
**Flammability:** At Normal Atmospheric Temperature and Pressure: Lower: N/A Upper: N/A  
**Partition Coefficient:** NOT APPLICABLE  
**Auto-ignition Temperature:** >450°C (per ASTM D1929)  
**Decomposition Temperature:** NOT APPLICABLE  
**Viscosity Units, Temp. (Method):** NOT APPLICABLE  
**Dry Point:** NOT APPLICABLE  
**Volatile Characteristics:** NOT APPLICABLE  
**Viscosity:** NOT APPLICABLE  
**Hazardous Polymerization:** NOT EXPECTED TO OCCUR  
**Other Chemical Reactivity:** NONE  
**Stability:** STABLE  
**Other Physical and Chemical Properties:** NONE

## SECTION 10: STABILITY AND REACTIVITY

**Stability/Instability:** Thermally stable at typical use temperatures.  
**Conditions to Avoid:** Avoid continuous exposure above 350°F (177°C), and do not exceed intermittent excursions above 375°F (191°C). Exposure to elevated temperatures can cause product to begin to char and decompose. Avoid direct sunlight.  
**Incompatible Materials:** Avoid contact with strong oxidizers.  
**Thermal Decomposition:** Decomposition products depend upon temperature, air supply and the presence of other materials. Toxic gases are released during decomposition.

## SECTION 11: TOXICOLOGICAL INFORMATION

**Hazardous Decomposition Products (Fire):** *LIKE WOOD AND OTHER ORGANIC MATERIALS CAN RELEASE TOXIC SMOKE IF IGNITED.*

**SECTION 12:** *Non-mandatory*

**SECTION 13:** *Non-mandatory*

**SECTION 14:** *Non-mandatory*

**SECTION 15:** *Non-mandatory*

## SECTION 16: OTHER INFORMATION

**Preparation:** This SDS was prepared in November 2017

**General Comments:** *SOME OF THE INFORMATION PRESENTED AND CONCLUSIONS DRAWN HEREIN ARE FROM SOURCES OTHER THAN DIRECT TEST DATA ON THE PRODUCT ITSELF.*

This product is not a "Hazardous Chemical" as defined by the OSHA Hazard Communication standard, 29 CFR 1910.1200

### **a. SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 (SARA), TITLE III**

*EXEMPT. APPENDIX H(4) SECTION 1910, 1200(b) AS A MANUFACTURED ITEM a), b), c), AND SECTION 311(e) #10.*

### **b. TOXIC SUBSTANCES CONTROL ACT (TSCA)**

*ALL COMPONENTS OF THIS PRODUCT ARE LISTED ON THE TSCA INVENTORY.*

### **c. COMPREHENSIVE ENVIRONMENTAL RESPONSE, COMPENSATION AND LIABILITY ACT (CERCLA)**

*NO CHEMICALS IN THIS PRODUCT ARE SUBJECT TO THE REPORTING REQUIREMENTS OF CERCLA.*

## **DISCLAIMER OF LIABILITY**

THE INFORMATION IN THIS SDS WAS OBTAINED FROM SOURCES WHICH WE BELIEVE ARE RELIABLE. HOWEVER, THE INFORMATION IS PROVIDED WITHOUT ANY WARRANTY, EXPRESS OR IMPLIED, REGARDING ITS CORRECTNESS.

THE CONDITIONS OR METHODS OF HANDLING, STORAGE, USE AND DISPOSAL OF THE PRODUCT ARE BEYOND OUR CONTROL AND MAY BE BEYOND OUR KNOWLEDGE. FOR THIS AND OTHER REASONS, WE DO NOT ASSUME RESPONSIBILITY AND EXPRESSLY DISCLAIM LIABILITY FOR LOSS, DAMAGE OR EXPENSE ARISING OUT OF OR IN ANY WAY CONNECTED WITH THE HANDLING, STORAGE, USE OR DISPOSAL OF THIS PRODUCT.