

Print Date: 07-09-2020

FOSTER 95-50
802438PM**SAFETY DATA SHEET**

REVISION DATE: 07-08-2020

SUPERSEDES: 02-19-2020

SECTION 1: IDENTIFICATION OF THE PRODUCT AND SUPPLIER**PRODUCT INFORMATION**

PRODUCT: FOSTER 95-50
 PRODUCT DESCRIPTION: Sealant
 INTENDED USE: Sealant
 PRODUCT IDENTIFIER: 802438PM

COMPANY INFORMATION

H.B. Fuller Company
 1200 Willow Lake Boulevard
 Vadnais Heights, MN 55110
 Telephone: 888-423-8553

Medical Emergency Phone Number (24 Hours): 1-888-853-1758
 Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

SECTION 2: HAZARDS IDENTIFICATION**GHS Hazard Symbols:**

GHS Signal Word: Warning
GHS Classification: Carcinogenicity Category 2; Hazardous to the aquatic environment - Acute Category 3; Flammable Liquid Category 4
GHS Hazard Phrases: Combustible Liquid; Suspected of causing cancer.; Harmful to aquatic life.
GHS Precautions:
Safety Precautions: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.
First Aid Measures: IF exposed or concerned: Get medical advice/attention. In case of fire: Use water spray, foam, dry chemical or carbon dioxide to extinguish.
Storage: Store in a well-ventilated place. Keep cool. Store locked up.
Disposal: Dispose of contents/container in accordance with local/regional/national/international regulation for chemical wastes.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

| Chemical Name | CAS # | PERCENT | Classification | Note |
|------------------------------|------------|---------|--------------------|---------------|
| Calcium carbonate | 471-34-1 | 30 - 50 | | * (see below) |
| Kaolin clay | 1332-58-7 | 10 - 30 | | * (see below) |
| Diatomaceous earth | 61790-53-2 | 1 - 5 | | * (see below) |
| Ethylene glycol:CAS:107-21-1 | 107-21-1 | 0.1 - 1 | Acute Tox. 4; H302 | |

SAFETY DATA SHEET

| | | | | |
|-----------------------|------------|---------|---|--------------|
| Titanium dioxide | 13463-67-7 | 0.1 - 1 | Carc. 2; H351 | *(see below) |
| Crystalline silica | 14808-60-7 | 0.1 - 1 | Carc. 1A; H350 STOT RE 1; H372 | *(see below) |
| Cristobalite | 14464-46-1 | 0.1 - 1 | Acute Tox. 4; H332 Carc. 2; H351 STOT RE 1; H372 | *(see below) |
| Xylene: CAS:1330-20-7 | 1330-20-7 | 0.1 - 1 | Aquatic Acute 1; H400 Acute Tox. 4; H332 | |
| Cumene | 98-82-8 | 0.1 - 1 | Aquatic Acute 1; H400 Aquatic Chronic 2; H411 Acute Tox. 4; H302 Carc. 2; H351 | |

*This product contains one or more materials that may be hazardous when present as an airborne dust. During normal handling of the product, the material is encapsulated within the product and will not present an exposure risk. Once the product has reached its final state and is abraded or disturbed, dusting and exposure may occur. This product contains titanium dioxide, which is hazardous when present as an airborne dust. As provided, and during normal use of this product, this substance is encapsulated within the product. As such, it is considered to be inextricably bound, and not readily available for exposure. This product contains crystalline silica. As provided, and during normal use of this product, the crystalline silica is encapsulated within the product. As such, it is considered to be inextricably bound, and not readily available for exposure. Use of this product would not subject the user to the compliance requirements of 29CFR1910.1053 or 1926.1153.

Unlisted ingredients are not 'hazardous' per the Occupational Safety and Health Administration Hazard Communication Standard (29 CFR 1910.1200) and/or are not found on the Canadian Workplace Hazardous Materials Information System ingredient disclosure list. See Section 8 for exposure limit guidelines.

SECTION 4: FIRST AID MEASURES

IF IN EYES: Use an eye wash to remove a chemical from your eye regardless of the level of hazard. Flush the affected eye for at least twenty minutes. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Seek medical advice after flushing.

IF ON SKIN: Wash with soap and water. Get medical attention if irritation develops or persists.

IF INHALED: Remove to fresh air. Restore breathing, if necessary. Call a physician if symptoms persist.

IF SWALLOWED: Do not induce vomiting. Seek medical attention if symptoms develop. Provide medical care provider with this MSDS.

SECTION 5: FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA:

Use water spray, foam, dry chemical or carbon dioxide.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Vapors are heavier than air and can travel to a source of ignition and flash back.

SPECIAL FIRE FIGHTING INSTRUCTIONS:

Persons exposed to products of combustion should wear self-contained breathing apparatus and full protective equipment.

HAZARDOUS COMBUSTION PRODUCTS:

Carbon dioxide, Carbon monoxide

SECTION 6: ACCIDENTAL RELEASE MEASURES

SPECIAL PROTECTION:

Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section 8 of this MSDS. Additional precautions may be necessary based on special circumstances created by the spill including; the material spilled, the

SAFETY DATA SHEET

quantity of the spill, the area in which the spill occurred. Evaporation of volatile substances can lead to the displacement of air creating an environment that can cause asphyxiation.

METHODS FOR CLEAN-UP: Scrape up and place in disposal container.
Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area.

Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

SECTION 7: HANDLING AND STORAGE

Handling: Avoid contacting and avoid breathing the material. Use only in a well ventilated area.
Keep away from heat, sparks and flame.
Wash thoroughly after handling.
Keep container closed.
Emptied container retains vapor and product residue.
Observe all labeled precautions until container is cleaned.
Drums of this material should be grounded when pouring.
DO NOT CUT OR WELD ON OR NEAR THIS CONTAINER.

Storage: Store in a cool, dry, ventilated location. Keep away from heat and flame. Keep container closed.

Consult the Technical Data Sheet for specific storage instructions.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

EXPOSURE LIMITS:

| Chemical Name | Note | ACGIH EXPOSURE LIMITS | OSHA PEL |
|--------------------|---------------|---|--|
| Calcium carbonate | * (see below) | No data available. | 15 mg/m ³ TWA (total dust); 5 mg/m ³ TWA (respirable fraction) |
| Kaolin clay | * (see below) | 2 mg/m ³ TWA (particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter) | 15 mg/m ³ TWA (total dust); 5 mg/m ³ TWA (respirable fraction) |
| Diatomaceous earth | * (see below) | No data available. | 20 mppcf TWA; ((80)/(% SiO ₂)) mg/m ³ TWA) |
| Titanium dioxide | * (see below) | 10 mg/m ³ TWA | 15 mg/m ³ TWA (total dust) |
| Crystalline silica | * (see below) | 0.025 mg/m ³ TWA (respirable particulate matter) | ((250)/(%SiO ₂ + 5) mppcf TWA (respirable)); ((10)/(%SiO ₂ + 2) mg/m ³ TWA (respirable)); ((30)/(%SiO ₂ + 2) mg/m ³ TWA (total dust)) |
| Cristobalite | * (see below) | 0.025 mg/m ³ TWA (respirable particulate matter) | 50 µg/m ³ TWA (listed under Respirable crystalline silica) |
| Cumene | | 50 ppm TWA | 50 ppm TWA; 245 mg/m ³ TWA Skin absorption may potentially contribute to the overall exposure to this material. |

*This product contains one or more materials that may be hazardous when present as an airborne dust. During normal handling of the product, the material is encapsulated within the product and will not present an exposure risk. Once the product has reached its final state and is abraded or disturbed, dusting and exposure may occur. This product contains titanium dioxide, which is hazardous when present as an airborne dust. As provided, and during normal use of this product, this substance is encapsulated within the product. As such, it is considered to be inextricably bound, and not readily available for exposure. This product contains crystalline silica. As provided, and during normal use of this product, the

SAFETY DATA SHEET

crystalline silica is encapsulated within the product. As such, it is considered to be inextricably bound, and not readily available for exposure. Use of this product would not subject the user to the compliance requirements of 29CFR1910.1053 or 1926.1153.

ENGINEERING CONTROL METHODS:

| | |
|-------------------------|--|
| VENTILATION: | Use local exhaust ventilation or other engineering controls to minimize exposures. |
| EYE PROTECTION: | Wear safety glasses when handling this product. |
| SKIN PROTECTION: | Avoid skin contact by wearing chemically resistant gloves. Skin absorption may potentially contribute to the overall exposure to this material. Appropriate measures should be taken to prevent absorption so that the TLV is not invalidated. |
| GLOVES: | Nitrile |
| RESPIRATORY PROTECTION: | Respiratory protection may be required to avoid overexposure when handling this product. Use a respirator if general room ventilation is not available or sufficient to eliminate symptoms. Respirators should be selected by and used following requirements found in OSHA's respirator standard (29 CFR 1910.134). |

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

| | |
|--|------------------------------|
| PHYSICAL STATE: | Semi-solid |
| COLOR: | Off-white |
| ODOR: | Solvent |
| ODOR THRESHOLD: | Not established |
| pH: | Not established |
| FREEZING/MELTING POINT (deg. C): | Not established |
| BOILING POINT (deg. C): | Not established |
| FLASH POINT: | 63°C; 145°F Pensky-Martens |
| EVAPORATION RATE: | Not established |
| FLAMMABILITY: | Not a flammable solid or gas |
| UPPER EXPLOSIVE LIMIT (% in air): | Not established |
| LOWER EXPLOSIVE LIMIT (% in air): | Not established |
| VAPOR PRESSURE (mm Hg): | Not established |
| VAPOR DENSITY: | Not established |
| WEIGHT PER GALLON (lbs.): | 11.90 |
| SPECIFIC GRAVITY: | 1.430 |
| SOLUBILITY: | Not established |
| OCTANOL/WATER COEFFICIENT: | Not established |
| AUTOIGNITION TEMPERATURE: | Not established |
| DECOMPOSITION TEMPERATURE: | Not established |
| VISCOSITY: | No data available. |
| SOLIDS (% by weight): | 73.0 |
| VOC, weight percent | 29.40 |
| VOC, U.S. EPA Method 24, less water and exempt solvents (theoretically determined) | 420g/liter of material |

SECTION 10: STABILITY AND REACTIVITY

| | |
|---------------------------|---------------------------------|
| STABILITY: | Stable under normal conditions. |
| CHEMICAL INCOMPATIBILITY: | Not established |
| HAZARDOUS POLYMERIZATION: | Will not occur. |

SAFETY DATA SHEET

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide

SECTION 11: TOXICOLOGICAL INFORMATION**Component Toxicity / Toxicology Data:**

| COMPONENT NAME | LD50/LC50 |
|--------------------------|--|
| Kaolin clay | Oral LD50 Rat > 5,000 mg/kg Dermal LD50 Rat > 5,000.00 mg/kg |
| Oil, petroleum | Oral LD50 Rat > 5,000 mg/kg Inhalation LC50 Rat 2,180.00 MG/M3 Dermal LD50 Rabbit > 2,000.00 mg/kg |
| Trimethylbenzene, 1,2,4- | Oral LD50 Rat 3,280 mg/kg Inhalation LC50 Rat 18.00 G/M3 Dermal LD50 Rabbit > 3,160.00 mg/kg |

This product is a mixture. Unless noted, the information below is based on components.

Skin corrosion / irritation: No irritation hazard in normal industrial use.

Serious eye damage / irritation :No irritation hazard in normal industrial use.

Respiratory / skin sensitization: No data available.

Germ cell mutagenicity: No data available.

Carcinogenicity: Contains a material that may cause cancer.

Reproductive toxicity: No data available.

Specific target organ toxicity-single exposure: No data available.

Respiratory irritation / Narcotic effects: No data available.

Specific target organ toxicity-repeated exposure: No data available.

Target organs potentially affected by exposure: Lungs Blood Central nervous system

Aspiration hazard: Not an aspiration hazard.

Medical Conditions Aggravated by Exposure: Lung disease, Blood disorders (like anemia)

SECTION 12: ECOLOGICAL INFORMATION

OVERVIEW: No ecological information available for this product.

MOBILITY: No data available.

PERSISTENCE: No data available.

BIOACCUMULATION: No data available.

This product has not been tested for ecological effects. Relevant information for components is listed below:

| Component: | Ecotoxicity values: |
|-------------------------------|--|
| Aromatic petroleum distillate | Acute Toxicity (Fish): LC50 Oncorhynchus mykiss 9.22 mg/L 96 h Acute Toxicity (Daphnia): EC50 Daphnia magna 6.14 mg/L 48 h Acute Toxicity (Algae): Not established |
| Bodied linseed oil | Acute Toxicity (Fish): LC50 96 h Danio rerio >1 mg/L Acute Toxicity (Daphnia): Not established Acute Toxicity (Algae): Not established |
| Trimethylbenzene, 1,2,4- | Acute Toxicity (Fish): LC50 Pimephales promelas 7.19 - 8.28 mg/L 96 h Acute Toxicity (Daphnia): EC50 Daphnia magna 6.14 mg/L 48 h Acute Toxicity (Algae): Not established |

SAFETY DATA SHEET**SECTION 13: DISPOSAL CONSIDERATIONS**

To the best of our knowledge, this product does not meet the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. Disposal via incineration at an approved facility is recommended as industry best practice. Consult state, local or provincial authorities for more restrictive requirements.

SECTION 14: TRANSPORT INFORMATION

Consult Bill of Lading for transportation information.

| | |
|---------|---------------|
| US DOT: | NOT REGULATED |
| IATA: | NOT REGULATED |
| IMDG: | NOT REGULATED |

SECTION 15: REGULATORY INFORMATION**INVENTORY STATUS**

| | |
|------------------------|--|
| U.S. EPA TSCA: | This product is in compliance with the Toxic Substances Control Act's Inventory requirements. |
| CANADIAN CEPA DSL: | The components of this product are included on the DSL or are exempt from DSL requirements. |
| EUROPEAN REACH: | As a result of the introduction of REACH into Europe, this product cannot be imported into Europe unless the REACH requirements are met. |
| AUSTRALIA AICS: | This product is in compliance with the Australian Inventory of Chemical Substances requirements. |
| JAPAN ENCS: | This product is in compliance with the Japanese Existing and New Chemical Substances requirements. |
| KOREAN TCCL: | This product is in compliance with the Korean Existing Chemicals List requirements. |
| PHILIPPINES: | This product is in compliance with the Philippine Inventory of Chemicals and Chemical Substances requirements. |
| CHINA IECSC INVENTORY: | This product is in compliance with the Inventory of Existing Chemical Substances in China (IECSC) requirements. |

If you need more information about the inventory status of this product call 651-236-5858.

This product may contain chemical substances that are regulated for export by various government agencies (such as the Environmental Protection Agency, the Bureau of Industry and Security, or the Drug Enforcement Administration, among others). Before exporting this product from the USA or Canada, we recommend you contact us at reg.request@hbfuller.com to request an export review.

FEDERAL REPORTING

*This product contains one or more materials that may be hazardous when present as an airborne dust. During normal handling of the product, the material is encapsulated within the product and will not present an exposure risk. Once the product has reached its final state and is abraded or disturbed, dusting and exposure may occur. This product contains titanium dioxide, which is hazardous when present as an airborne dust. As provided, and during normal use of this product, this substance is encapsulated within the product. As such, it is considered to be inextricably bound, and not readily available for exposure. This product contains crystalline silica. As provided, and during normal use of this product, the crystalline silica is encapsulated within the product. As such, it is considered to be inextricably bound, and not readily available for exposure. Use of this product would not subject the user to the compliance requirements of 29CFR1910.1053 or 1926.1153.

Print Date: 07-09-2020

FOSTER 95-50
802438PM**SAFETY DATA SHEET**

EPA SARA Title III Section 313

Unless listed below, this product does not contain toxic chemical(s) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR part 372. EPA has advised that when a percentage range is listed the midpoint may be used to fulfill reporting obligations.

| Chemical Name | CAS# | % |
|------------------------|---------|---------|
| 1,2,4-Trimethylbenzene | 95-63-6 | 1 - 5 |
| Cumene | 98-82-8 | 0.1 - 1 |

STATE REPORTING

Proposition 65, The Safe Drinking Water and Toxic Enforcement Act of 1986:

Unless listed below, this product does not contain known levels of any chemical known to the State of California to cause cancer or reproductive harm.

| Chemical Name/List | CAS | Percent |
|---------------------------------------|------------|---------|
| Titanium dioxide (Carcinogen) | 13463-67-7 | 0.1 - 1 |
| Quartz (Carcinogen) | 14808-60-7 | 0.1 - 1 |
| Cumene (Carcinogen) | 98-82-8 | 0.1 - 1 |
| Ethylene glycol (Developmental toxin) | 107-21-1 | 0.1 - 1 |

Substances of Very High Concern (SVHC) Content:

Unless listed below, this product does not contain SVHC's at 0.1% or greater, as of the version date of this SDS.

SECTION 16: OTHER INFORMATION

SDS VERSION DATE: 07-08-2020

This Safety Data Sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200) and the Canadian Workplace Hazardous Materials Information System (WHMIS).

HMIS RATING: HEALTH -- 2 FLAMMABILITY -- 2 REACTIVITY -- 0

See SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for personal protective equipment recommendations.

Prepared by: The Global Regulatory Department

Phone: 651-236-5842

The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to H.B. Fuller Construction Products, Inc. from its suppliers, and because H.B. Fuller Construction Products, Inc. has no control over the conditions of handling and use, H.B. Fuller Construction Products, Inc. makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and H.B. Fuller Construction Products, Inc. assumes no responsibility for use or reliance thereon. It is the responsibility of the user of H.B. Fuller Construction Products, Inc. products to comply with all applicable federal, state and local laws and regulations.